

# CARE AND CLEANING INSTRUCTIONS FOR MAGNETIC CAR SIGNAGE

FAILURE TO FOLLOW ANY OF THE FOREGOING INSTRUCTIONS MAY RESULT IN DAMAGE TO THE PRODUCT ITSELF AND TO THE SURFACE ON WHICH THE PRODUCT IS AFFIXED, AND MAY ALSO INCREASE THE LIKELIHOOD THAT THE PRODUCT WILL NOT ADHERE PROPERLY AND MAY FALL OFF DURING USE. NEITHER JLP COMPANY INC NOR ANY OF ITS OFFICERS, DIRECTORS, OR OTHER AFFILIATES WILL BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY CLAIMS, LOSSES OR OTHER DAMAGES TO THE PRODUCT, THE SURFACE TO WHICH IT IS AFFIXED, OR ANY OTHER PROPERTY OR PERSON, INCLUDING WITHOUT LIMITATION DAMAGES FOR PERSONAL INJURY, CAUSED BY ANY ABUSE OR MISUSE OF THE PRODUCT OR OTHER FAILURE TO FOLLOW THE INSTRUCTIONS.

## PREPARING THE PRODUCT AND THE CAR DOOR:

- Clean the car paint surface and the magnetic material with a mild detergent. Wipe with a soft cloth and allow to dry.
- Wax the magnetized side of the magnet sign as well as the vehicle and wait until the wax is dried/cured around 48 hrs.
- Clean again the surface of the vehicle and the magnet sign with mild detergent.
- Apply the magnet sign onto the flat surface of the car and check for uneven surface to avoid lifted corners that may cause air gaps that can lead to the sign being blown off when car is moving at high speed.
- REMOVE the car sign WEEKLY and follow the steps explain above before reapplying the sign to ensure optimal result and any DAMAGES.

For best results, apply the Product at room temperature.

Use care in handling the Product in extremely cold conditions, as the magnetic material can become brittle.

Long-term outdoor usage of magnets on painted surfaces may result in fading, due to shielding the underlying color from ultraviolet rays.

Make sure to remove the car door magnet from any vehicle before a car wash.